



TONGUE & GROOVE • SHIPLAP • SIDING

WP4-R Tongue & Groove 1x6
1x8

WP-11 Shiplap 1x6
1x8

Dolly Varden 1x8

#105 Drop Siding 1x8

Latia Tongue & Groove
J-Grade SPF 2x6

Tongue & Groove Select Decking 2x6

Log Cabin Siding 2x8



Add beauty and warmth to any home with natural wood siding and flooring. Arizona Pine products are milled to exact tolerances from kiln dried pine. They're perfect for a variety of interior and exterior applications. Installation is easy and all materials are ready for paint, stain or clear coating.

For quality and consistency, select Arizona Pine.

For best results, always follow installation guidelines. See reverse side.



Handling and Installation Guidelines

Arizona Pine siding products are manufactured from kiln dried Pine to minimize the effects of swelling and shrinking. But as with all lumber products, care in handling and installation delivers the best results. To ensure your complete satisfaction with Arizona Pine products, we recommend the following:

1. Precondition (acclimate) Arizona Pine material for 10 days to two weeks by storing it in the room where it will be installed.
2. Prior to installation, prime or pre-finish side, edges and ends (after pre-conditioning). This reduces the appearance of unfinished lines resulting from further shrinkage that may occur following installation.
3. Apply by nailing at least 1-1/2" directly in to wood or other "nailable" substrate. Use stainless, high-tensile aluminum or hot-dipped galvanized 6d finishing nails for interior applications; 8d for exterior.
4. For 1"X 6" fasten as shown to conceal nails. For 1"x 8" also use face nailing.

