



TechTrim™ uses the latest in polymer science and technology for a trim board that's better than wood and other trim products. It's designed for top performance that resists the rigors of the elements, providing great looks year after year, and it carries a 25-year limited warranty.

TechTrim is lighter than other materials, easy to install and offers low-maintenance durability that makes TechTrim the trim board of choice for quality-minded installers and homeowners alike

Available in these nominal sizes:

1" x 4", 6", 8" and 5/4" x 4", 6", 8" available in 16' lengths.

1" x 10", 12" and 5/4" x 10", 12" available in 12' lengths.





Won't absorb water

Because of its polymer composition, TechTrim™ is impervious to moisture, unlike wood or cement trim. It repels wetness like a suit of armor – absolutely none can get in. With TechTrim, paint won't bubble or peel from moisture, and that means homeowners get years of outstanding performance.

Won't rot, warp, crack or suffer from insect attack

TechTrim will retain its look and finish. No splintering. No rotting. No cracking. That means fewer problems for the homeowner – and fewer callbacks and headaches for the contractor. What's more, TechTrim is impervious to insects.

Reversible surface

A unique reversible surface makes TechTrim versatile. On one side you'll find an elegant woodgrain finish. The other side is smooth. Both finishes are compatible with cement and vinyl siding.

Factory primed, ready to paint

TechTrim requires no special preparation for painting. No sanding. No scuffing. The factory-primed finish allows paint to go on quickly and smoothly. And it often needs only one coat of quality latex paint to finish the job. Tell us that's not beautiful. Want to use a dark color? No problem for TechTrim. In fact, dark colors are our specialty.



TechTrim™ is easy to install

- Use conventional high-speed, carbide-tipped blades and cut quickly for best results.
- TechTrim can be nailed directly to structural members or applied over siding, provided the fasteners used penetrate 1" into structural members.
- Use corrosion-resistant nails and double-nail narrow widths at least every 16" o.c.;
 10" and 12" wide TechTrim should be triple-nailed.



- Proper spacing is required for all joints. Refer to complete installation instructions for spacing requirements.
- TechTrim is factory primed on four sides and typically is finished with one coat of quality exterior latex paint applied within 90 days.

Read and understand the printed installation instructions included with every TechTrim unit shipped from the factory or visit www.techtrimproducts.com for complete installation instructions.

www.techtrimproducts.com

Technology finally hits home.™

25-Year Limited Warranty

TechTrim™ is warranted for a period of twenty-five (25) years from the date of your original purchase. The product will maintain its nail- and screw-holding characteristics and will not crack, chip, rot or delaminate. Warranty is void if product is not appropriately painted within 90 days of installation. Please visit our Web site for complete warranty information.

Refer to installation instructions from your dealer for specific guidelines.



877.463.8379

UFP Ventures II, Inc. 1801 E. Lessard Prairie du Chien, WI 53821

www.techtrimproducts.com

©2006-2008 Universal Forest Products, Inc. All rights reserved. Printed in the USA. 3419 4/08